

# DKM 2500.1.3 K



**VERTICAL LATHE**

# DKM 2500.1.3 K

## SPECIFICATIONS

|                                                                |                              |
|----------------------------------------------------------------|------------------------------|
| <b>working diameter max</b>                                    | 2500 mm                      |
| <b>processingshöhe max</b>                                     | 1310 mm                      |
| <b>max. workpiece weight</b>                                   | 13000 Kg                     |
| <b>Diameter of Table</b>                                       | 2200 mm                      |
| <b>speeds</b>                                                  | 2 - 62 mm/min (16 steps)     |
| <b>feeds longitudinal/cross</b>                                | 0.24 - 145 mm/min (18 steps) |
| <b>quick feed cross</b>                                        | 2160 mm/min                  |
| <b>Crossbeam support X-axis travel</b>                         | 1210 mm                      |
| <b>crossbeam vertical travel</b>                               | 800 mm                       |
| <b>toolholder for lathe</b>                                    |                              |
| <b>lateralr Stahlhaltersupport movement of X-axis</b>          | 630 mm                       |
| <b>lateralr toolholder for lathesupport movement of Z-axis</b> | 1150 mm                      |
| <b>quick feed of Traverse</b>                                  | 350 mm/min                   |
| <b>rated capacity</b>                                          | 37 KW                        |
| <b>weight</b>                                                  | 24.400,00 kg                 |
| <b>dimensions</b>                                              | 5500x6960x5025 mm            |



## ACCESSOIRES

Ball leadscrews + servo drives the axis