

Zyklendrehmaschine DKM 630/1000 LT

Zyklendrehmaschine with 12-fold tool turret for live tools and heavilyem Servomotor and 3 gear steps. The repeat accuracy of the tool changers liegt at 0,008 mm. high rapid feed speed of X=4 m/min and Z=5 m/min.

Price upon inquiry

specifications

height of center	325 mm
distance between center	1000 mm
max. swing over bed	650 mm
max. swing over slider	375 mm
diameter of spindlehole	105 mm
spindlenose	A1-11
speed range	10 - 850 U/min 3 gear steps
movement of X-axis	370 mm
movement of Z-axis	760 mm
rapid feed Z-axis	5 m/min
rapidfeed X-Axis	4 m/min
quill diameter	100 mm
quill stroke	250 mm
quill konus	morse cone 5
power of engine	11 KW
weight	4.000,00 kg
dimensions	3300x1900x1900 mm

equipment

- 12-fold tool changer for live tools
- automatic central lubrication
- Fanuc Oi-MATE or Siemens 828D control system
- RS-232 interface
- 2 Movable doors with viewing window

accessoires

FANUC MATE Oi or SIEMENS 828D control system, electronical Handle wheel, 12-fold tool changer for live tools, central lubrication, cooling device, . german Operating documents